PRODUCT INFORMATION



Lubricants – Transmission Oils – Automotive

Version: 264/01 Valvoline[™] ATF Pro 236.14

Premium full synthetic high performance automatic transmission fluid for passenger cars, vans, LCV, and SUV.

Valvoline ATF Pro 236.14 provides superior protection and lubrication of the automatic gearbox over a wide temperature range.

O.E.M. approvals	
MB-Approval 236.14	

Performance levels

MB 236.12 MB NAG-2 transmissions MB 7-speed automatic transmission series 722.9 MB 5-speed automatic transmission series 722.6 Ssang Yong passenger cars with MB automatic transmissions

Features & Benefits

Superior protection

Superior protection against wear and tear, also under high stress working conditions.

Advanced additives

Superior additives protect against corrosion, oxidation, foaming, and deposits.

Breakdown resistance

Premium synthetic base oils, balanced additive system avoid breakdowns and stick-slip even after long-time use.

Consistent, stable viscosity

Superior viscosity-temperature properties even at very low temperatures. Highly stable viscosity over a long period.

Enhanced friction properties

Premium fully synthetic base oils, viscosity index improvers, and friction modifiers result in outstanding friction properties for smoother shifting. In addition, the product resists aging and has excellent thermal stability.

Applications

Suitable for automatic gearboxes of passenger cars, vans, LCD, and SUV when the manufacturer recommends an ATF according to MB 236.14 and MB 236.12.

Can be used in MB NAG-2 transmissions.

Suitable for Ssang Yong passenger cars with MB automatic transmissions.

VALVOLINE EUROPE WIELDRECHTSEWEG 39 3316 BG DORDRECHT NETHERLANDS

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvolineeurope.com

Typical properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline ATF Pro 236.14	
Colour	Red
Viscosity, mm²/s @ 100 °C.	6,4
DIN 51562-1	
Viscosity, mm²/s @ 40 °C.	29,6
DIN 51562-1	
Viscosity Index	185
DIN ISO 2909	
Pour Point, ºC	-51
DIN ISO 3016	
Specific Gravity @ 15.6°C.	0,848
DIN 51757	
Flash Point, COC, ºC.	>200
DIN ISO 2592	

This information only applies to products manufactured in the following location(s): Europe

Health & Safety

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet http://msds.valvoline.com

Protect the environment

Take used oil to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces -

™ Trademark of Valvoline, registered in various countries © 2016

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

VALVOLINE EUROPE WIELDRECHTSEWEG 39 3316 BG DORDRECHT NETHERLANDS