# PRODUCT INFORMATION



Automotive Chemicals - Technical Sprays - Cleaning

Version: TS/001

### Valvoline™ EGR Cleaner

High quality exhaust gas recirculation cleaner to dissolve deposits in the EGR valve, air intake system, manifold and inlet valves. To restore the air flow to the engine, improving power and acceleration and reducing exhaust smoke.

#### **Applications**

EGR valve Air intake system Manifold Inlet valve

#### **Product characteristics**

Fast acting Leaves no residue Prevents the deposits of resin 360° valve

#### Directions for use:

Before use, carefully read the directions on the packaging. For professional use only.

Valvoline™ EGR Cleaner should be at room temperature before use. The processing temperature should be between 5 to 30°C. Shake before use.

Please refer to the owner's manual for the location of the hardware.

Loosen the hose between the turbo and air intake system.

Start the engine and allow to run at approx. 2000 rpm.

Spray Valvoline™ EGR Cleaner directly into the inlet of the manifold by repeatedly, briefly pressing the nozzle till the engine runs more smoothly.

Install the hose.

## PRODUCT INFORMATION



#### Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com** 

#### **Typical properties**

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Valvoline™ EGR Cleaner	
Contents	500 ml
Basis	Solution of
	organic
	solvents
VOC-content	100% w/w
Relative density at 20°C	0,73 g/ml
Yield	2 – 3 g/sec
Vapour pressure at 20°C	2,5 to 3,5 bar

This information only applies to products manufactured in the following location(s): Europe

#### **Health & Safety**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet http://sds.valvoline.com

#### Protect the environment

Take used chemicals to an authorized collection point. Comply with local regulations. Do not discharge into drains, soil or water.

#### Storage

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

Replaces -

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ellis Enterprises B.V. and its affiliates assume legal responsibility.

<sup>™</sup> Trademark of Valvoline, registered in various countries © 2018